UTILITY PATENT APPLICATION TRANSMITTAL *(Only for new nonprovisional applications under 37 CFR 1.53(b))*	Attorney Docket No.	0039-7669-2S
	First Inventor or Application Identifier	Eiji SAWA, et al.
	Title	METHOD AND APPARATUS FOR INSPECTING PATTERNS

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents	ADDRESS TO:	Assistant Commissioner for Patents Box Patent Application Washington, DC 20231

1. ■ Fee Transmittal Form (e.g. PTO/SB/17) *(Submit an original and a duplicate for fee processing)*

2. ■ Specification   Total Pages   **51**

3. ■ Drawing(s) *(35 U.S.C. 113)*   Total Sheets   **10**

4. ■ Oath or Declaration   Total Pages   **2**

   a. ■ Newly executed (original)

   b. ☐ Copy from a prior application *(37 C.F.R. §1.63(d))* *(for continuation/divisional with box 15 completed)*

     i. ☐ DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference *(usable if box 4B is checked)* The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4B, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

ACCOMPANYING APPLICATION PARTS

6. ■ Assignment Papers (cover sheet & document(s))

7. ☐ 37 C.F.R. §3.73(b) Statement *(when there is an assignee)*   ☐ Power of Attorney

8. ☐ English Translation Document *(if applicable)*

9. ☐ Information Disclosure Statement (IDS)/PTO-1449   ☐ Copies of IDS Citations

10. ☐ Preliminary Amendment

11. ■ White Advance Serial No. Postcard

12. ☐ Small Entity Statement(s)   ☐ Statement filed in prior application. Status still proper and desired.

13. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*

14. ■ Other: Notice of Priority

15. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below:

   ☐ Continuation   ☐ Divisional   ☐ Continuation-in-part (CIP)   of prior application no.:

   Prior application information: Examiner: Group Art Unit:

16. Amend the specification by inserting before the first line the sentence:

   ☐ This application is a   ☐ Continuation   ☐ Division   ☐ Continuation-in-part (CIP) of application Serial No.   Filed on

   ☐ This application claims priority of provisional application Serial No.   Filed

17. CORRESPONDENCE ADDRESS

OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C.
FOURTH FLOOR
1755 JEFFERSON DAVIS HIGHWAY
ARLINGTON, VIRGINIA 22202
(703) 413-3000
FACSIMILE: (703) 413-2220

Name:	Marvin J. Spivak	Registration No.:	24,913
Signature:		Date:	3/29/00
Name:		Registration No.:	

TITLE OF THE INVENTION

METHOD AND APPARATUS FOR INSPECTING PATTERNS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Applications No. 11-089332, filed March 30, 1999; and
No. 11-261912, filed September 16, 1999, the entire
contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to a defect
inspection of an object such as a mask or a reticle
of a semiconductor wafer. More particularly, the
invention relates to a method and apparatus for
inspecting an auxiliary pattern (e.g., OPC: optical
proximity correction pattern) formed on a mask or the
like in order to enhance the resolution at the time of
light exposure.

Further, the invention relates to a method
and apparatus for inspecting a mask, a reticle,
a semiconductor wafer, a semiconductor chip and
a semiconductor circuit in which a pattern related
to semiconductor production is formed, or a sample
such as a printed substrate, a liquid crystal display
substrate. More particularly, the invention relates to
a method and apparatus for inspecting a pattern to find
defects, therein, dust thereon and the like.

In a step of manufacturing a semiconductor device,

for example, an exposure apparatus performs exposure
on the semiconductor substrate, by using a mask or
a reticle.   The circuit pattern transferred to the
semiconductor substrate becomes smaller year by year.

5   Due to the limited resolution of the exposure apparatus,
the circuit pattern transferred to the substrate has
rounded corners and edges as is illustrated in FIG. 1.

To perform exposure to provide on the substrate
a pattern which is identical to the design pattern,

10   an auxiliary pattern is now made in a mask or the like,
as is shown in FIG. 2.

A mask having an auxiliary pattern is inspected.
More specifically, the data representing the real
pattern obtained by photographing the auxiliary pattern

15   is compared with the data representing the design
pattern, thereby to determine whether the patter has
defects or not.

Circuit patterns are made smaller and smaller as
described above, and the resolution of the real pattern

20   obtained by photographing of the circuit pattern is
approaching the width of each element of the real
pattern.   In other words, the pattern precision is
increasing.   Thus, in a method in which differential is
effected to detect the direction of a corner or an edge

25   and real pattern data and design pattern data are
compared, the position shift may occur between real
pattern data and the design data.   This inevitably

lower the accuracy of pattern inspection.

BRIEF SUMMARY OF THE INVENTION

Accordingly, the object of the present invention is to provide a method and apparatus for which can inspect a pattern with high accuracy without a position shift between real pattern data and design data.

In order to attain the above object, according to a first aspect of the present invention, there is provided a pattern inspection method comprising acquiring difference data by subtracting a real pattern window having real pattern data corresponding to predetermined pixels of the real pattern data obtained by imaging an inspection object from a design pattern window corresponding to the real pattern window and shift design pattern windows which are obtained by shifting the design pattern windows in a plurality of directions, respectively; selecting one window from the design pattern window and shift design pattern windows such that the selected one window has a minimum difference data; and performing a pattern inspection of the inspection object based on a difference value between the selected one window and the real pattern window.

According to a second aspect of the invention, there is provided a pattern inspection method according to the first aspect, wherein the acquiring step, selecting step and performing step are repeatedly

executed with respect to all pixels of the real pattern data.

According to a third aspect of the invention, there is provided a pattern inspection method according to the first aspect, wherein the plurality of directions are eight directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°, 315° with respect to a noticed pixel of the real pattern window.

According to a fourth aspect of this invention, there is provided a pattern inspection method according to the first aspect, wherein the performing step comprises: selecting a central pixel of the selected one window obtaining a difference value between the selected central pixel and a central pixel of the window of the real pattern data, and determining a defect of the inspection object by comparing the obtained difference value between the selected central pixel of the selected one window and a threshold value set in advance.

According to a fifth aspect of the present invention, there is provided a pattern inspection method according to the first aspect, wherein a shift width of the shifted design pattern windows is within one pixel.

According to a sixth aspect of the invention, there is provided a pattern inspection method according to the first aspect, wherein the performing step

comprises: obtaining a difference value by subtracting
a noticed pixel of the selected one window and
predetermined pixels surrounding the noticed pixel
of the selected one window from a noticed pixel of
the real pattern window and predetermined pixels
surrounding the noticed pixel of the real pattern
window, outputting 1) a "0" difference value in
a case where the obtained difference value is within
a difference value obtained by shifting the design
pattern window by one pixel or less, 2) a difference
value obtained by subtracting the minimum value from
the obtained difference value in a case where the
obtained difference value is less than a minimum value
of difference values obtained by shifting the design
pattern window and 3) a difference value obtained by
subtracting a maximum value of difference values which
are obtained by shifting the design pattern window by
one pixel or less from the obtained difference value in
a case where the obtained difference value is lager
than the maximum value, and performing the pattern
inspection of the inspection object by comparing the
outputted difference value with a threshold value set
in advance.

    According to a seventh aspect of the invention,
there is provided a pattern inspection method according
to the first aspect, wherein the difference value is
determined based on a lightness of pixels in the real

pattern data and a lightness of pixels in the design pattern data.

According to an eighth aspect of this invention, there is provided a pattern inspection device comprising: means for acquiring difference data by subtracting a real pattern window having real pattern data corresponding to predetermined pixels of the real pattern data obtained by imaging an inspection object from a design pattern window corresponding to the real pattern window and shift design pattern windows which are obtained by shifting the design pattern windows in a plurality of directions, respectively; means for selecting one window from the design pattern window and shift design pattern windows such that the selected one window has a minimum difference data; and means for performing a pattern inspection of the inspection object based on a difference value between the selected one window and the real pattern window.

According to a ninth aspect of the invention, there is provided a pattern inspection device according to claim 8, wherein the acquisition of the difference data by the means for acquiring, selection of the selected on window by the means for selecting and pattern inspection performed by the means for performing are repeatedly executed with respect to all pixels of the real pattern data.

According to a tenth aspect of this invention,

there is provided a pattern inspection device according
to the eighth aspect, wherein the plurality of
directions are eight directions of 0°, 45°, 90°, 135°,
180°, 225°, 270°, 315° with respect to a noticed pixel
5   of the real pattern window.

According to an eleventh aspect of the present
invention, there is provided a pattern inspection
device according to the eighth aspect, wherein
the performing step comprises: means for selecting
10   a central pixel of the selected one window, obtaining
a difference value between the selected central pixel
and a central pixel of the window of the real pattern
data, and determining a defect of the inspection object
by comparing the obtained difference value between
15   the selected central pixel of the selected one window
and a threshold value set in advance.

According to a twelfth aspect of the invention,
there is provided a pattern inspection device according
to the eighth aspect, wherein a shift width of the
20   shifted design pattern windows is within one pixel.

According to a thirteenth aspect of the invention,
there is provided a pattern inspection device according
to the eighth aspect, wherein the means for performing
comprises obtaining a difference value by subtracting
25   a noticed pixel of the selected one window and
predetermined pixels surrounding the noticed pixel
of the selected one window from a noticed pixel

of the real pattern window and predetermined pixels
surrounding the noticed pixel of the real pattern
window, outputting 1) a "0" difference value in
a case where the obtained difference value is within
5   a difference value obtained by shifting the design
pattern window by one pixel or less, 2) a difference
value obtained by subtracting the minimum value from
the obtained difference value in a case where the
obtained difference value is less than a minimum value
10   of difference values obtained by shifting the design
pattern window and 3) a difference value obtained by
subtracting a maximum value of difference values which
are obtained by shifting the design pattern window by
one pixel or less from the obtained difference value in
15   a case where the obtained difference value is lager
than the maximum value, and performing the pattern
inspection of the inspection object by comparing the
outputted difference value with a threshold value set
in advance.

20   According to a fourteenth aspect of the present
invention, there is provided a pattern inspection
device according to the eighth aspect, wherein the
difference value is determined based on a lightness of
pixels in the real pattern data and a lightness of
25   pixels in the design pattern data.

           According to a 15th aspect of the present
invention, there is provided a method of manufacturing

a mask comprising: preparing a substrate with a light
shielding film on which a mask pattern is formed;
and inspecting the substrate with the light shielding
film on which a mask pattern is formed, wherein the
inspecting step comprises: acquiring difference data by
subtracting a real pattern window having real pattern
data corresponding to predetermined pixels of the real
pattern data obtained by imaging the mask pattern from
a design pattern window corresponding to the real
pattern window and shift design pattern windows which
are obtained by shifting the design pattern windows in
a plurality of directions, respectively; selecting one
window from the design pattern window and shift design
pattern windows such that the selected one window has
a minimum difference data; and performing a pattern
inspection of the mask pattern based on a difference
value between the selected one window and the real
pattern window.

According to a 16th aspect of the present
invention, there is provided a method according to
the 15th aspect, wherein the acquiring step, selecting
step and performing step are repeatedly executed with
respect to all pixels of the real pattern data.

According to a 17th aspect of the present
invention, there is provided a method according to the
15th aspect, wherein the plurality of directions are
eight directions of 0°, 45°, 90°, 135°, 180°, 225°,

270°, 315° with respect to a noticed pixel of the real pattern window.

According to a 18th aspect of the present invention, there is provided a method according to the 15th aspect, wherein the performing step comprises: selecting a central pixel of the selected one window, obtaining a difference value between the selected central pixel and a central pixel of the window of the real pattern data, and determining a defect of the mask pattern by comparing the obtained difference value between the selected central pixel of the selected one window and a threshold value set in advance.

According to a 19th aspect of the present invention, there is provided a method according to the 15th aspect, wherein a shift width of the shifted design pattern windows is within one pixel.

According to a 20th aspect of the present invention, there is provided a method according to the first aspect5, wherein the performing step comprises: obtaining a difference value by subtracting a noticed pixel of the selected one window and predetermined pixels surrounding the noticed pixel of the selected one window from a noticed pixel of the real pattern window and predetermined pixels surrounding the noticed pixel of the real pattern window, outputting 1) a "0" difference value in a case where the obtained difference value is within a difference value obtained

by shifting the design pattern window by one pixel or less, 2) a difference value obtained by subtracting the minimum value from the obtained difference value in a case where the obtained difference value is less than a minimum value of difference values obtained by shifting the design pattern window and 3) a difference value obtained by subtracting a maximum value of difference values which are obtained by shifting the design pattern window by one pixel or less from the obtained difference value in a case where the obtained difference value is lager than the maximum value, and performing the pattern inspection of the mask pattern by comparing the outputted difference value with a threshold value set in advance.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combina- tions particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illust- rate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred

embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a diagram showing a corner or the like of a circuit pattern, which is rounded due to the limited resolution of an exposure apparatus;

FIG. 2 is a diagram showing a corner or the like of a circuit pattern, which is formed in the case an auxiliary pattern is formed;

FIG. 3 is a block diagram showing a pattern-inspecting apparatus according to a first embodiment of the present invention;

FIG. 4 represents an algorithm of correcting a position shift in the pattern-inspecting apparatus;

FIG. 5 is a flow chart illustrating how the apparatus perform various processes;

FIG. 6 is a schematic representation of design pattern data of a 5 × 5 window which has been shifted in a plurality of directions;

FIG. 7 is a diagram for explaining how the inspection is repeated, each time to inspect one of the pixels of real pattern data;

FIG. 8 is a flowchart for explaining a manufacturing process of the photo mask;

FIG. 9 is a block diagram of a pattern-inspecting device according to a second embodiment of the invention;

FIG. 10 is a flow chart showing the operation of

the pattern-inspecting apparatus;

FIG. 11A is a diagram illustrating a standard image;

FIG. 11B is a diagram showing the standard image shifted to the left by 1/2 pixel;

FIG. 11C is a diagram showing the standard image shifted to the right by 1/2 pixel;

FIG. 11D is a diagram showing the standard image shifted to the left by 1/4 pixel;

FIG. 11E is an image showing operation results;

FIG. 12 is a block diagram showing an inspection apparatus; and

FIG. 13 is a flow chart explaining the process of obtaining the difference obtained by the pattern-inspecting apparatus according to a second embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention will now be described with reference to the accompanying drawings.

[First Embodiment]

FIG. 3 is a block diagram of a pattern-inspecting apparatus according to the first embodiment of the present invention.

An image device 1 is, for example, an area sensor 21 or the like. The image device 1 is designed to input an image of an object 2, such as a photo mask, and output an image signal representing the object 2.

A real pattern memory 4 is connected to an A/D converter 3, which in turn is connected to the output terminal of the image device 1. The A/D converter 3 converts the image signal output from image device 1, to digital data, or real pattern data. The real pattern data is stored into the real pattern memory 4.

A design data generation section 5 is designed to develop the design data of the object 2 having an auxiliary pattern, into a bit pattern. The section 5 receives position data corresponding to an acquiring position of digital signal as an image signal which is output from area sensor 22. The section 5 then generates design pattern data representing a circuit pattern or the like that is formed in the object 2, by using the position data. The design pattern data thus prepared is stored into a design pattern memory 6. The design pattern memory 6 stores design pattern data which has been generated on the assumption that the real pattern is rounded at corners and edges when formed by exposure performed based on the design data.

To the real pattern memory 4 and design pattern memory 6, a window extraction sections 7, 8 are connected respectively. To one window extraction section 7, a difference operation section 11 is connected via delay sections 9 and 10. To the other window extraction section 8, the difference operation section 11 is connected via a shift direction operation

section 12 and a selection section 13.

The window extraction section 7 has the function
of extracting the real pattern data of a window of
5 × 5 pixels (5 × 5 window, hereinafter) with
a noticed pixel located in the center, for example,
in order to accomplish a local inspection based
on the real pattern data stored in the real pattern
memory 4.

The delay section 9 delays the image data
extracted by the window extraction section 7, by
the time corresponding to the process time spent in
the shift direction operation section 12. The next
delay section 10 delays the image data supplied from
the delay section 9, by the time corresponding to
the process time spent in the selection section 13,
and supplies the data to the difference operation
section 11.

The window extraction section 8 has the function
of extracting the design pattern data of a window of
7 × 7 pixels (7 × 7 window, hereinafter), for example.
The section 8 supplies the data to the shift direction
operation section 12 in order to effect a local
inspection in accordance with the design pattern data
stored in the design pattern memory 6.

The shift direction operation section 12 has
the function of receiving the design pattern data of
the 7 × 7 window extracted by the window extraction

section 8. The section 12 also has the function of
preparing, based on the design pattern and design
pattern data of nine windows. The nine windows are:
a basic 5 × 5 window with a noticed pixel in the center
and eight 5 × 5 windows. The eight 5 × 5 windows are
obtained by shifting the basic 5 × 5 window data by,
for example, 1/2 pixel, in eight directions of 0°, 45°,
90°, 135°, 180°, 225°, 270°, 315°. The section has
another function of obtaining the data representing the
difference between the design pattern data and the real
pattern data. The shift direction operation section 12
shifts the window by 1/2 pixel from the sum ratio of
adjacent pixels when the window of the design pattern
data is shifted in the eight directions of 0°, 45°,
90°, 135°, 180°, 225°, 270°, 315°.

The selection section 13 has the function of
selecting the design pattern data in the direction
in which the total of the pixels is minimum, that is,
the total of the pixels is closest to 0 among the
difference data found by the shift direction operation
section 12. In other words, the section 13 selects the
design pattern whose position has been corrected with
respect to the real pattern data S_{ij}, among the
difference data found by the shift direction operation
section 12.

The difference operation section 11 has the
function of obtaining the difference between a central

pixel of the window of the design pattern data selected
by the selection section 13, and a central pixel of
the window of the real pattern data from the delay
section 10.

5   A defect judgement section 14 has the function of
comparing the difference supplied from the difference
operation section 11 with the threshold set in advance,
thereby determining whether defects exist in the
object 2.

10   A repetitive execution section 15 has the function
of causing the shift direction operation section 12,
selection section 13, difference operation section 11,
and defect judgement section 14 to repeat the process
of inspecting the pattern of the object 2, for all the

15   pixels of the real pattern data.

        The operation of the apparatus so constructed as
described above will be explained below, with reference
to FIG. 4 that shows the algorithm for correcting
the position shift.

20   The image device 1 inputs an image of the object 2
such as a photo mask, and outputs the image signal
thereof. The A/D converter 3 converts the image signal
to digital data, or real pattern data. The real
pattern data is stored into the real pattern memory 4.

25   The design data generation section 5 develops the
design data of the object 2, in which an auxiliary
pattern is formed, into a bit pattern. The section 5

also inputs position data corresponding to a drawing
position of the digital signal as the image signal
the image device 1 has output. The section 5 prepares
the design pattern data representing a circuit pattern

5   or the like formed in the object 2, by using the
position data. The design pattern data is stored into
the design pattern memory 6.

The flow of the inspection the pattern-inspecting
apparatus will be described below, with reference to

10   the schematic diagram of FIG. 5.

The real pattern data stored in the real pattern
memory 4 is called Sij, while the design pattern data
stored in the design pattern memory 6 is called Rij.

In the step #1, the window extraction section 7

15   extracts the real pattern data of a 5 × 5 window with
a noticed pixel K located in the center, from the real
pattern data Sij stored in the real pattern memory 4.
The real pattern data of the 5 × 5 window extracted
by the section 7 is delayed by the delay section 9,

20   by the time corresponding to the process time spent
in the shift direction operation section 12 described
below. The real pattern data is then delayed by
the time corresponding to the process time spent
in the selection section 13, by the delay section 10.

25   The real pattern data, thus delayed, is supplied to
the difference operation section 11.

Then, in the step #2, the other window extraction

section 8 extracts the design pattern data of a 7 × 7
window from the design pattern data Rij stored in the
design pattern memory 6. The design pattern data is
supplied to the shift direction operation section 12.

5   In the step #3, the shift direction operation
section 12 receives the design pattern data Rij of
the 7 × 7 window extracted by the window extraction
section 8. The section 12 prepares design pattern data
Qij of the total of 9 windows form the design pattern

10   data Rij. Of these nine windows, the first is a basic
5 × 5 window with a noticed pixel located in the center.
The other eight windows have been by shifting the
design pattern data of the basic window by 1/2 pixel,
in eight directions of 0°, 45°, 90°, 135°, 180°, 225°,

15   270°, 315°, respectively. The shift direction
operation section 12 shifts the window by 1/2
pixel from the sum ratio of adjacent pixels when
the window of the design pattern data is shifted in
the eight directions of 0°, 45°, 90°, 135°, 180°, 225°,

20   270°, 315°.

FIG. 6 schematically shows how the design pattern
data of the above nine 5 × 5 windows is obtained.
In FIG. 6, the design pattern data Qij of the 5 × 5
window with the noticed pixel K in the center is shown

25   as shifted in the shift direction -1 from the design
pattern data Rij. Similarly, the design pattern data
of the 5 × 5 window obtained from the 5 × 5 window

shifted by 1/2 pixel in the direction of the angle of
90° is shown as shifted in the shift direction -2.
Likewise, the design pattern data Qij of the 5 × 5
window obtained from the 5 × 5 window shifted by 1/2
5   pixel in the direction of the angle of 0° is shown as
shifted in the shift direction -3; the design pattern
data Qij of the 5 × 5 window obtained from the 5 × 5
window shifted by 1/2 pixel in the direction of
the angle of 270° is shown as shifted in the shift
10   direction -4; the design pattern data Qij of the 5 × 5
window obtained from the 5 × 5 window shifted by 1/2
pixel in the direction of the angle of 180° is shown as
shifted in the shift direction -5; the design pattern
data Qij of the 5 × 5 window obtained from the 5 × 5
15   window shifted by 1/2 pixel in the direction of the
angle of 45° is shown as shifted in the shift direction
-6; the design pattern data Qij of the 5 × 5 window
obtained from the 5 × 5 window shifted by 1/2 pixel in
the direction of the angle of 315° is shown as shifted
20   in the shift direction -7; the design pattern data Qij
of the 5 × 5 window obtained from the 5 × 5 window
shifted by 1/2 pixel in the direction of the angle of
225° is shown as the time of the shift direction -8;
and the design pattern data Qij of the 5 × 5 window
25   obtained from the 5 × 5 window shifted by 1/2 pixel in
the direction of the angle of 135° is shown as shifted
in the shift direction -9. The closer each window is

to the center, the higher the priority order of its
shift direction. The priority order of the 5 × 5
windows, each having a noticed pixel K located in
the center, is: the direction of the angle of 90°,

5   the direction of the angle of 0°, the direction of
the angle of 270°, the direction of the angle of 180°,
the direction of the angle of 45°, the direction of
the angle of 315°, the direction of the angle of 225°,
and the direction of the angle of 135°.

10   The shift direction operation section 12 supplies
the design pattern data Qij of the 5 × 5 windows of the
shift directions -1 to -9, to the difference operators
12-1 to 12-9, which find the difference between the
real pattern data Sij and the design pattern data Qij.

15   The difference is given as:

$$\Sigma (ABS|Sij-Qij|)$$

     In the step #5, the selection section 13 selects
the central pixels Sij and Qij of the design pattern
data in the direction in which the total of the pixels

20   is minimum, that is, the total of the pixels is closest
to 0, from the difference data found by the shift
direction operation section 12.

     The position of the central pixels Sij and Qij of
the design pattern data selected as described above is

25   corrected with respect to the real pattern data Sij.
That is, the position of the design pattern data Rij is
corrected, which has been prepared on the assumption

that the circuit pattern is rounded at corners and
edges at the time of exposure, with respect to
a mechanical position shift and the real pattern
data Sij. Accordingly, the real pattern data Sij

5   and the design pattern data Rij are matched in position
for the corners and edges of the circuit pattern.

The difference operation section 11 finds the
difference between the central pixels Sij and Qij of
the design pattern data selected by the selection

10 section 13, and the difference between the central
pixels Sij and Qij of the windows of the real pattern
data from the delay section 10. The section 12 then
supplies the differences to the defect judgement
section 14.

15 In the step #6, the defect judgement section 14
compares the difference supplied from the difference
operation section 11 with the threshold value set
in advance. If the difference is greater than the
threshold value, the defect section 14 determines that

20 the pattern of the object 2 has a defect. The flow
then goes to the step #7, in which a defect process
is performed. If the difference supplied from
the section 11 is smaller than the threshold value,
the defect judgement section 14 determines that

25 the pattern of the object 2 has no defects and is
therefore a normal one.

In the step #8, the repetitive execution section

15 determines whether the pattern inspection for
all pixels of the real pattern data Sij has completed
or not. If the section 15 determines that the
inspection has not completed, if proceeds to the
5   step #9 and shifts a noticed pixel K by one pixel
as shown in FIG. 7. The, the flow returns to the
step #1, whereby the steps of inspecting the pattern
of the object 2 are sequentially effected by the
shift direction operation means 12, selection
10   section 13, difference operation section 11 and
defect judgement section 14, for all the pixels of
the real pattern data.

       If the pattern inspection is completed for all the
pixels of the real pattern data Sij, the flow goes to
15   the step #10. In Step #10, the next object 2 is set,
the real pattern data of the object 2 is stored into
the real pattern memory 4, and the above-described
pattern inspection is carried out.

       In the first embodiment described above, the
20   differences between the real pattern data Sij, on
the one hand, and the basic design pattern data Rij of
the 5 × 5 window, with a noticed pixel located in the
center, obtained from the design pattern data Rij, and
the 5 × 5 windows obtained from the basic window and
25   shifted in a plurality of directions such as the eight
directions of the angles of 0°, 45°, 90°, 135°, 180°,
225°, 270°, 315°, on the other hand, is found.

The design pattern data in the direction, in which the
total of the pixels is minimum, is selected among the
differences, in accordance with the differences between
the central pixels Sij and Qij of the selected design
pattern data, on the one hand, and central pixels Sij
and Qij of the windows of the real pattern data the
pattern inspection of the object 2, on the other hand.
Therefore, it is possible to correct the position shift
which may cause a pseudo-defect even in the OPC pattern
close to the pixel resolving power. Hence, the pattern
inspection can be accomplished with high accuracy
without a position shift between the real pattern data
and the design data. Moreover, it is possible to
decrease the number of pseudo-defects resulting from
a position shift, because the real pattern data is
detected locally and sequentially using 5 × 5 windows.

    As to the position shift between the design
pattern data and the real pattern data, defects lower
than the pixel resolving power can be detected.
This is because the design pattern data is shifted in
a plurality of directions by a 1/2 pixel, which is one
pixel or less.

    The present invention is not limited to the above
embodiment. Rather, it can be modified as will be
described as follows.

    In the embodiment described above, the 7 × 7
windows are extracted from the design pattern data Rij

to carry out the local inspection. Instead, the window
size may be determined from the real pattern data S_{ij}
and the magnification of the optical system, and
windows of 9×9 pixels or windows of 11×11 pixels

5   may be used.

In the shift direction operation section 11, the
windows are shifted in each direction by a 1/2 pixel.
Alternatively, the windows may be shifted by one
pixel or less, in accordance with the shift amount

10   between the real pattern data S_{ij} and the design
pattern data R_{ij}.

As has been described above in detail, this
invention can provide a pattern-inspecting method and
a pattern-inspecting apparatus, which effect inspect

15   patterns with high accuracy without a position shift
between the real pattern data and the design data.

Next, where a photo mask is used as the inspection
object, the method for manufacturing the photo mask
will be described.

20   FIG. 8 is a flowchart for explaining a
manufacturing process of the photo mask.

In the manufacturing process of the photo mask,
as shown in FIG. 8, a Cr light shielding film is
formed on a substrate such as a silica glass by

25   evaporation (S1).

An then, the mask pattern is formed by irradiating
the Cr light shielding film formed on the substrate

with an electron beam (S2). Next, the inspection of the mask pattern is performed in accordance with above described inspection process (S3), and it is determined whether or not the mask pattern has a defect (S4).

5   In step 4, if it is determined that the mask pattern has a defect, the defect is recovered (S5) and the process of manufacturing the mask pattern is terminated (S6). Furthermore, in step 4, if it is determined that the mask pattern has not defect, the

10   process is terminated (S6).

<Second Embodiment>

In the first embodiment, the central pixel of the design pattern window is selected so that the total of the pixels may be minimum, and the difference between

15   the selected central pixel and the central pixel of the real pattern window is found, and the difference and the threshold value are compared, thereby determining whether or not an object has defects.

In the second embodiment, the process is the same

20   as in the first embodiment, before the design pattern window is selected so that the total of the pixels may be minimum. The second embodiment differs in the method of determining the presence or absence of defects in accordance with the difference between the

25   selected design pattern window (non-defective pattern) and the real pattern window.

The pattern-inspecting apparatus according to the

second embodiment will be described below.

FIG. 9 is a block diagram of the pattern-inspecting apparatus according to the second embodiment of the present invention. The same sections as shown in FIG. 3 are designated at the same reference numerals.

The pattern-inspecting apparatus according to this embodiment differs from the first embodiment shown in FIG. 3 in that an inspection pattern memory 131 and a non-defective pattern memory 132 are used in place of the real pattern memory 4 and the design pattern memory 6, respectively.

As described above, the difference between this embodiment and the first embodiment resides in the difference operation method after a window is selected. The pattern-inspecting apparatus according to the second embodiment may have the structure shown in FIG. 3.

An image device 1, having a CCD area sensor 21 or the like, has the function of inputting an image of an object 2 such as a semiconductor chip formed on a semiconductor wafer, and outputting an image signal thereof.

To the output terminal of the image device 1, an inspection pattern memory 131 and a non-defective pattern memory 132 are connected by an A/D converter 3. When the image device 1 scans the object 2, it generates an image signal. The A/D converter 3 converts

the image signal to digital inspection pattern data.
The inspection pattern data is stored into the
inspection pattern memory 131.

When the image device 1 scans a non-defective
product made by using a non-defective semiconductor
wafer selected in advance, it generates an image signal.
The A/D converter 3 converts the image signal to
digital data. The digital data is stored into the
non-defective pattern memory 132 as non-defective
pattern data.

To the inspection pattern memory 131 and the
non-defective pattern memory 132, two window extraction
sections 7 and 8 are connected respectively.

To one window extraction section 7, a difference
operation section 11 is connected by delay sections 9
and 10. To the other window extraction section 8,
a difference operation section 11 is connected through
a shift direction operation section 12 and a selection
section 13.

The window extraction section 7 has the function
of extracting the inspection pattern data of a window
of 5 × 5 pixels (5 × 5 window, hereinafter) with
a noticed pixel in the center, for example, and
supplying the data to the delay section 9 in order to
carry out a local inspection of the inspection pattern
data stored in the inspection pattern memory 4.

The delay section 9 delays the image data

extracted by the window extraction section 7 by
the time corresponding to the process time in the shift
direction operation section 12, while the next delay
section 10 has a function of delaying the image data
5   from the delay section 9 by the time corresponding
to the process time in the selection section 13,
and supplying the data to the difference operation
section 11.

The window extraction section 8 has the function
10   of extracting the non-defective pattern data of
a window of 7 × 7 pixels (7 × 7 window, hereinafter),
for example, and supplying the data to the shift
direction operation section 12 in order to carry out
a local inspection based on the non-defective pattern
15   data stored in the non-defective pattern memory 132.

The shift direction operation section 12 has the
function of receiving the non-defective pattern data of
the 7 × 7 window extracted by the window extraction
section 8. Based on the non-defective pattern data,
20   the section 12 prepares non-defective pattern data of
nine 5 × 5 window. More precisely, it prepares a basic
pattern data of noticed pixel located in the center
and pattern data of eight 5 × 5 windows, obtained by
shifting the basic non-defective pattern data in eight
25   directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°,
315°, for example, by a 1/2 pixel. The section 12 then
find the difference data between the non-defective

pattern data and the inspection pattern data.

In this case, the shift direction operation section 12 shifts the window by a 1/2 pixel from the sum ratio of adjacent pixels when the window of the non-defective pattern data is shifted in the eight directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°, 315°.

The selection section 13 has the function of selecting the non-defective pattern data in the direction in which the total of the pixels is minimum, that is, the total of the pixels is closest to 0 among the difference data found by the shift direction operation section 12. In other words, the non-defective pattern data the position of which is corrected with respect to the inspection pattern data, among the difference data found by the shift direction operation section 12.

The difference operation section 11 finds the maximum value and the minimum value in the position of a notice pixel when the standard image is shifted from the noticed pixel of the standard image and the surrounding pixels thereof. If the difference between the noticed pixel of the inspection image and the noticed pixel of the standard image in the range between the maximum value found and the minimum value found, the difference operation section 11 determines that the difference is a noise, and does not output

the difference.

A defect judgement section 14 has the function of comparing the difference from the difference operation section 11 with the threshold set in advance, thereby determining whether or not the object 2 has defects.

A repetitive execution section 15 has the function of repetitively performing a series of treatments of inspecting the pattern of the object 2 by the shift direction operation section 12, selection section 13, difference operation section 11, and defect judgement section 14, with respect to all the pixels of the inspection pattern data.

The operation of the supplying so constituted is described below.

The image device 1 uses a non-defective semiconductor wafer as a object, and inputs the image of the object such as a circuit pattern formed in the semiconductor wafer and outputs the image signal thereof.

The image signal output by the apparatus 1 is converted by the A/D converter 3, to non-defective pattern data. This non-defective pattern data is stored into the non-defective pattern memory 132.

Then, a general semiconductor chip, a object 2, is inspected. That is, the image device 1 inputs the image of a circuit pattern formed in the object 2 and so on, and outputs the image signal thereof. The image

signal output by the image device 1 is converted by the
A/D converter 3, to digital inspection pattern data.
The inspection pattern data is stored into the
inspection pattern memory 131.

5   By the comparison of the inspection pattern data
and the non-defective pattern data, the inspection of
the object 2 is carried out.

       The operation of the pattern-inspecting apparatus
will be described below, in accordance with the flow

10   chart shown in FIG. 10. As described above, a non-
defective semiconductor chip is used as the object 2.
An object such as a circuit pattern formed in the
semiconductor chip is scanned by the image device 1 in
advance.`

15   Then, the image scanned by the image device 1
is converted by the A/D converter 3, to non-defective
pattern data. The non-defective pattern data is
input to the non-defective pattern memory 132. Thus,
the image signal is stored in the non-defective pattern

20   memory 4 as non-defective pattern data. The image of
the object 2 is scanned by the image device 1, and
is converted by the A/D converter 3, to inspection
image data. The inspection image data is input to
the inspection pattern memory 131 as an inspection

25   image (S1).

       The position of the inspection pattern data input
in the inspection pattern memory 131 is corrected

with respect to the non-defective pattern data, which
is the standard image stored in the non-defective
pattern memory 132 (S2). Then, the brightness of
the inspection pattern data is measured and is

5   normalized (S3). The non-defective pattern data
and the inspection pattern data of the standard
image are compared and thereby the difference is
detected (S4).

        The difference detection is described with

10   reference to FIG. 11A through FIG. 11E and a flow chart
in FIG. 13, in the case of the one-dimensional data.
The shift in this case is a 1/2 pixel.

        FIG. 11A shows the standard image, FIG. 11B shows
the standard image shifted in the left direction by

15   a 1/2 pixel, FIG. 11C shows the standard image shifted
in the right direction by a 1/2 pixel, FIG. 11D shows
the inspection image shifted in the left direction by
a 1/4 pixel, and FIG. 11E shows the operation result.

        With respect to the standard image shown in

20   FIG. 11A, and the standard images obtained by the
standard image being shifted by a 1/2 pixel shown in
FIG. 11B and FIG. 11C, the sum of the difference
between the noticed pixel and the surrounding pixels of
the inspection image, which is the inspection pattern

25   data shown in FIG. 11D, and corresponding pixels with
respect to the standard image and shifted standard
image is calculated.

In the case of a window of 3 × 3 pixels,
for example, for nine images, the difference between
corresponding pixels is calculated, and the total is
found. The difference between the corresponding pixels
5   of the standard image or the shifted standard image
when the images are closest to the noticed pixel
and the surrounding pixels of the inspection image
is found (S11). At the same time, the maximum value
and the minimum value possible in the position of
10   the noticed pixel when the standard image is shifted
are found (S12), on the basis of the noticed pixel
and the surrounding pixels of the standard image.
Since the standard image is shifted by a 1/2 pixel,
the maximum and minimum errors occur when the standard
15   image is shifted by a 1/4 pixel, half of 1/2.

If the difference from the inspection image is
grater than the maximum value possible or smaller than
the minimum value possible when the standard image is
shifted, the value obtained by the maximum value or
20   the minimum value being subtracted from the difference
is output. Accordingly, when there is the closest
correspondence, the resulting difference doe not have
such a value as shown in FIG. 11E, with respect to the
inspection image shown in FIG. 11D. That is, if the
25   resulting difference is in the range between the
maximum value and the minimum value, the difference
is determined to be a noise, and no value is output

(the difference "0" is output).

If the difference is greater than the maximum value, output the value obtained by the maximum value being subtracted from the difference (S14). And if the difference is smaller than the maximum value, it is determined whether the difference is smaller or than the minimum value or not (S15).

If the difference is smaller than the minimum value, output the value obtained by the minimum value being subtracted from the difference (S16). And if the difference is smaller than the minimum value, output the value "0" (S17).

Then, the above difference is binarized in the binary system (S5), and the size is determined from the result in the binary system (S6), and the resulting image is displayed (S7).

When the process is completed with respect to one object 2, the repetitive execution section 15 performs the photographing of the next object 2. The same process is repeated, thereby inspecting the object 2. The non-defective pattern data need not be prepared each time by the scanning of the non-defective, but the non-defective pattern data stored in the non-defective pattern memory 132 may be used.

If in the method according to the present invention a two-dimensional image is used, the shift is a 1/2 pixel, a surrounding range is 3 $\times$ 3 pixels, and

the primary interpolation is carried out between the
pixels, the expression is as follows. The standard
image is R(x, y), the inspection image is P(x, y), and
the image of the operation result is Q(x, y).

$$R_{min} = \min_{m=-1,0,1,\ n=-1,-,1} \left\{ \frac{1}{4}(R(x+m, y+n) + 3 \cdot R(x, y)) \right\} - R(x, y)$$

$$R_{max} = \max_{m=-1,0,1,\ n=-1,-,1} \left\{ \frac{1}{4}(R(x+m, y+n) + 3 \cdot R(x, y)) \right\} - R(x, y)$$

$$T(x, y) = P(x, y) - R(x+m, y+n) \text{ ; when}$$
$$m=-\frac{1}{2},0,\frac{1}{2}, n=-\frac{1}{2},0,\frac{1}{2} \left\{ \sum_{s=-1}^{1} \sum_{t=-1}^{1} \left| P(x+s, y+t) - R(x+s+m, y+t+n) \right| \right\}$$

$$Q(x, y) = \begin{cases} \begin{cases} T(x, y) - R_{min} ; \text{if } T(x, y) < R_{min} \\ 0; \text{if } R_{min} < T(x, y) < R_{max} \\ T(x, y) - R_{max} ; \text{if } R_{max} < T(x, y) \end{cases} ; \text{if } (m = 0 \text{ and } n = 0) \\ \begin{cases} T(x, y) + R_{max} ; \text{if } T(x, y) < -R_{max} \\ 0; \text{if } -R_{max} < T(x, y) < -R_{min} \\ T(x, y) + R_{min} ; \text{if } -R_{min} < T(x, y) \end{cases} ; \text{else} \end{cases}$$

As was described above, the method according to
the present invention is equivalent to determining the
position delicately in the range of one pixel or less.
Therefore, errors can be made smaller. As a result,
defects with a small lightness difference can be
extracted. Accordingly, in the method in prior art in
which the maximum value - the minimum value in the

surroundings is referred to, errors which may result from a position shift by one pixel or less were large. Defects with a small lightness difference could not be extracted, but the method according to the present invention can overcome the shortcomings.

In the method according to the present invention, simple and correct detection is possible irrespective of the way the standard image is given. This is because the maximum error possible is calculated based on one pixel. Thus, a large number of images treated in advance which the statistical method in prior art required is unnecessary.

In the method according to the present invention, defects can be extracted at the optimum threshold and even defects with a small lightness difference can be extracted irrespective of the standard image pattern, since the threshold varies at an edge and in a flat portion. In the local movement method according to prior art, if the threshold is set so that no noises may be produced where there is an edge, though few errors owing to the position shift occur in a flat portion, only defects with the lightness difference greater than the threshold are detected. Thus, the method according to the present invention can solve the problem.

The case, wherein the above inspection technique is used in a chip appearance inspection device, will

be described. FIG. 12 is a block diagram showing
an outline of a chip appearance inspection treatment.

   An inspection table 223 on which a object 222 is
put consists of an XY stage 224 and a θ stage 225 on

5 the XY stage 224. With the inspection table 223,
a loader 226 which carries a semiconductor wafer, which
is the object 222, and an unloader 227 which delivers
a semiconductor wafer are connected.

   Above the inspection table 223 there is a Z stage

10 228, which has half mirrors 232a, 232b, 232c which
lead a reflected light axis to a coaxial dark field
illumination 229, an eyepiece 230, and an observation
color camera 231 respectively. A ring lighting 233 is
put where the ring lighting 233 can illuminate the

15 surface of the inspection table 223.

   On the light axis of the Z stage 228 and behind
the axis there is a CCD camera 234 with high resolution.
To the CCD camera 234, an image processing unit 235 is
connected. The image processing unit 235 is connected

20 with a control section 236. To the control section 236,
a driver 237 and a monitor 238 are connected which
control motors (not shown) which drive the XY stage 224,
the θ stage 225 and the Z stage 228.

   The device so constituted operates as follows:

25 first, a semiconductor wafer, which is a object 222,
is taken out of a magazine not shown and is carried by
the loader 226, and put on the inspection table 223.

As to the position shift of the semiconductor wafer
on the inspection table 223, the rotation shift is
corrected by the θ stage 225 and the center shift is
corrected by the XY stage 224. And the fine alignment
5   of the lens system is corrected by auto focus if
necessary.

Then the specified illumination is lighted, and
the inspection table 223 is moved to the first
measurement position. Thereby part of an image of
10   several chips or one chip is enlarged and drawn in the
image processing unit 235. In the image processing
unit 235 non-defective image data by a non-defective
semiconductor wafer (not shown) is prepared in advance
before the inspection using a learning pattern function.
15   Since the data is stored, the data is used to determine
the position of the image of the semiconductor wafer,
which is the object 222. Then, the CCD camera 234
scans the image and the image processing unit 235,
generating data. The data is compared with the non-
20   defective image data. The quality of the object 222 .
The treatment in the image processing unit 235 is
carried out using the above inspection method.

The same operation is repeated thereafter,
and when all the measurement is completed, the
25   semiconductor wafer on the inspection table 223 is
delivered by the unloader 227, and is put in the
magazine not shown.

Thus according to this device, it is possible in the inspection of a semiconductor chip to detect with certainty a defect with little noise and with a small lightness difference.

Although in the above embodiment the according to the present invention is used in the semiconductor chip inspection device, the present invention can be applied not only in the semiconductor chip inspection device but also in a mask or reticle inspection device, or an inspection device of a print base or a liquid crystal base and so on.

According to the present invention, even in the case of an inspection image with a position shift of one pixel or less, it is possible to detect with certainty a defect with little noise and a small lightness difference.

Because the maximum error possible which the standard image can take is calculated based on one image, a simple and correct defect detection is possible irrespective of the way in which the standard image is given.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the

spirit or scope of the general inventive concept as
defined by the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. A pattern inspection method comprising:

acquiring difference data by subtracting a real pattern window having real pattern data corresponding to predetermined pixels of the real pattern data obtained by imaging an inspection object from a design pattern window corresponding to the real pattern window and shift design pattern windows which are obtained by shifting the design pattern windows in a plurality of directions, respectively;

selecting one window from the design pattern window and shift design pattern windows such that the selected one window has a minimum difference data; and

performing a pattern inspection of the inspection object based on a difference value between the selected one window and the real pattern window.

2. The pattern inspection method according to claim 1,

wherein the acquiring step, selecting step and performing step are repeatedly executed with respect to all pixels of the real pattern data.

3. The pattern inspection method according to claim 1,

wherein the plurality of directions are eight directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°, 315° with respect to a noticed pixel of said real pattern window.

4. The pattern inspection method according to claim 1,

wherein the performing step comprises:

selecting a central pixel of the selected one window

obtaining a difference value between the selected central pixel and a central pixel of the window of said real pattern data, and

determining a defect of the inspection object by comparing the obtained difference value between the selected central pixel of the selected one window and a threshold value set in advance.

5. The pattern inspection method according to claim 1,

wherein a shift width of the shifted design pattern windows is within one pixel.

6. The pattern inspection method according to claim 1,

wherein the performing step comprises:

obtaining a difference value by subtracting a noticed pixel of the selected one window and predetermined pixels surrounding the noticed pixel of the selected one window from a noticed pixel of the real pattern window and predetermined pixels surrounding the noticed pixel of the real pattern window,

outputting 1) a "0" difference value in a case where the obtained difference value is within a

difference value obtained by shifting the design
pattern window by one pixel or less, 2) a difference
value obtained by subtracting the minimum value from
the obtained difference value in a case where the

5   obtained difference value is less than a minimum value
of difference values obtained by shifting the design
pattern window and 3) a difference value obtained by
subtracting a maximum value of difference values which
are obtained by shifting the design pattern window by

10   one pixel or less from the obtained difference value in
a case where the obtained difference value is lager
than the maximum value, and

      performing the pattern inspection of the
inspection object by comparing the outputted difference

15   value with a threshold value set in advance.

      7.   The pattern inspection method according to
claim 1,

      wherein the difference value is determined based
on a lightness of pixels in the real pattern data and a

20   lightness of pixels in the design pattern data.

      8.   A pattern inspection device comprising:

      means for acquiring difference data by subtracting
a real pattern window having real pattern data
corresponding to predetermined pixels of the real

25   pattern data obtained by imaging an inspection object
from a design pattern window corresponding to the real
pattern window and shift design pattern windows which

are obtained by shifting the design pattern windows in
a plurality of directions, respectively;

means for selecting one window from the design
pattern window and shift design pattern windows such
that the selected one window has a minimum difference
data; and

means for performing a pattern inspection of the
inspection object based on a difference value between
the selected one window and the real pattern window.

9. The pattern inspection device according to
claim 8,

wherein the acquisition of the difference data by
the means for acquiring, selection of the selected on
window by the means for selecting and pattern
inspection performed by the means for performing are
repeatedly executed with respect to all pixels of the
real pattern data.

10. The pattern inspection device according to
claim 8,

wherein the plurality of directions are eight
directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°,
315° with respect to a noticed pixel of said real
pattern window.

11. The pattern inspection device according to
claim 8,

wherein the performing step comprises:

means for selecting a central pixel of the

selected one window,

obtaining a difference value between the selected central pixel and a central pixel of the window of said real pattern data, and

5   determining a defect of the inspection object by comparing the obtained difference value between the selected central pixel of the selected one window and a threshold value set in advance.

12. The pattern inspection device according to
10   claim 8,

wherein a shift width of the shifted design pattern windows is within one pixel.

13. The pattern inspection device according to claim 8,

15   wherein the means for performing comprises

obtaining a difference value by subtracting a noticed pixel of the selected one window and predetermined pixels surrounding the noticed pixel of the selected one window from a noticed pixel of the
20   real pattern window and predetermined pixels surrounding the noticed pixel of the real pattern window,

outputting 1) a "0" difference value in a case where the obtained difference value is within a
25   difference value obtained by shifting the design pattern window by one pixel or less, 2) a difference value obtained by subtracting the minimum value from

the obtained difference value in a case where the
obtained difference value is less than a minimum value
of difference values obtained by shifting the design
pattern window and 3) a difference value obtained by
subtracting a maximum value of difference values which
are obtained by shifting the design pattern window by
one pixel or less from the obtained difference value in
a case where the obtained difference value is lager
than the maximum value, and

performing the pattern inspection of the
inspection object by comparing the outputted difference
value with a threshold value set in advance.

14.   The pattern inspection device according to
claim 8,

wherein the difference value is determined based
on a lightness of pixels in the real pattern data and a
lightness of pixels in the design pattern data.

15.   A method of manufacturing a mask comprising:

preparing a substrate with a light shielding film
on which a mask pattern is formed; and

inspecting the substrate with the light shielding
film on which a mask pattern is formed,

wherein the inspecting step comprises:

acquiring difference data by subtracting a real
pattern window having real pattern data corresponding
to predetermined pixels of the real pattern data
obtained by imaging the mask pattern from a design

pattern window corresponding to the real pattern window
and shift design pattern windows which are obtained by
shifting the design pattern windows in a plurality of
directions, respectively;

5   selecting one window from the design pattern
window and shift design pattern windows such that the
selected one window has a minimum difference data; and
       performing a pattern inspection of the mask
pattern based on a difference value between the
10   selected one window and the real pattern window.
       16.   The method according to claim 15,
       wherein the acquiring step, selecting step and
performing step are repeatedly executed with respect to
all pixels of the real pattern data.
15   17.   The method according to claim 15,
       wherein the plurality of directions are eight
directions of 0°, 45°, 90°, 135°, 180°, 225°, 270°,
315° with respect to a noticed pixel of said real
pattern window.
20   18.   The method according to claim 15,
       wherein the performing step comprises:
       selecting a central pixel of the selected one
window,
       obtaining a difference value between the selected
25   central pixel and a central pixel of the window of said
real pattern data, and
   determining a defect of the mask pattern by

comparing the obtained difference value between the selected central pixel of the selected one window and a threshold value set in advance.

19. The method according to claim 15,

wherein a shift width of the shifted design pattern windows is within one pixel.

20. The method according to claim 15,

wherein the performing step comprises:

obtaining a difference value by subtracting a noticed pixel of the selected one window and predetermined pixels surrounding the noticed pixel of the selected one window from a noticed pixel of the real pattern window and predetermined pixels surrounding the noticed pixel of the real pattern window,

outputting 1) a "0" difference value in a case where the obtained difference value is within a difference value obtained by shifting the design pattern window by one pixel or less, 2) a difference value obtained by subtracting the minimum value from the obtained difference value in a case where the obtained difference value is less than a minimum value of difference values obtained by shifting the design pattern window and 3) a difference value obtained by subtracting a maximum value of difference values which are obtained by shifting the design pattern window by one pixel or less from the obtained difference value in

a case where the obtained difference value is lager than the maximum value, and

performing the pattern inspection of the mask pattern by comparing the outputted difference value with a threshold value set in advance.

ABSTRACT OF THE DISCLOSURE

The difference data between the real pattern data S_{ij}, and a 5 × 5 window with a noticed pixel in the center and the design pattern data R_{ij} obtained by the design pattern data of the window being shifted in a plurality of directions with respect to the design pattern data R_{ig} is found by a shift direction operation section, and the design pattern data in the direction in which the total of the pixels is minimum is selected from the difference data by a selection section, the difference between the central pixels S_{ij}, Q_{ij} of the selected design pattern data and the central pixels S_{ij}, Q_{ij} of the windows of the real pattern data is found by a difference operation section, and the difference and a threshold are compared in a defect judgment section, and thereby the pattern inspection of the object is carried out.

FIG. 1 (PRIOR ART)

MASK   BAKING BY EXPOSURE

FIG. 2 (PRIOR ART)

MASK   BAKING BY EXPOSURE

AUXILIARY PATTERN   BAKING BY EXPOSURE

FIG. 3

1 IMAGE DEVICE

3 A/D

4 REAL PATTERN MEMORY

7 WINDOW EXTRACTION SECTION

9 DELAY

10 DELAY

11 DIFFERENCE OPERATION SECTION

14 DEFECT JUDGEMENT SECTION

THRESHOLD

5 DESIGN DATA GENERATION SECTION

6 DESIGN PATTERN MEMORY

8 WINDOW EXTRACTION SECTION

12 SHIFT DIRECTION OPERATION SECTION

13 SELECTION SECTION

15 REPETITIVE EXECUTION SECTION

DESIGN DATA

POSITION DATA

21

2

22

START

| MAKING A 5×5 WINDOW (Sij) FROM REAL PATTERN | #1 |

| MAKING A 7×7 WINDOW (Rij) FROM DESIGN PATTERN | #2 |

| MAKING NINE 5×5 WINDOWS (Qij) FROM (Rij) | #3 |

| CALCULATE Σ ABS | Sij−Qij | | #4 |

| SELECT CENTRAL PIXELS Sij, Qij OF WINDOWS HAVING MINIMUM VALUE | #5 |

#6

(Sij, Qij) : THRESHOLD

MORE THAN → DEFECT TREATMENT #7

LESS THAN

#8

FINAL PIXEL?

YES → ACQUIRE NEXT REAL PATTERN

#10

NO

SHIFT NOTICED PIXEL BY ONE PIXEL #9

FIG. 4

FIG. 5

SHIFT DIRECTION-6

SHIFT DIRECTION-3

SHIFT DIRECTION-7

SHIFT DIRECTION-2

SHIFT DIRECTION-1

SHIFT DIRECTION-4

SHIFT DIRECTION-9

SHIFT DIRECTION-5

SHIFT DIRECTION-8

DESIGN PATTERN
7×7 WINDOW

K

i

j

SHIFT DIRECTION
AND PRIORITY ORDER

FIG. 6

K   Sij

FIG. 7

IMAGE INPUT	S1
POSITION CORRECTION	S2
BRIGHTNESS NORMALIZATION	S3
DIFFERENCE	S4 ← STANDARD IMAGE
CONVERT DIFFERENCE INTO BINARY VALUE	S5
SIZE JUDGEMENT	S6
DISPLAY RESULTING IMAGE	S7

FIG.10

```
┌─────────────────────────────────┐
│ FORM LIGHT SHIELDING FILM ON    │──S1
│ SUBSTRATE                       │
└─────────────────────────────────┘
              │
              ▼
┌─────────────────────────────────┐
│     DRAW MASK PATTERN           │──S2
└─────────────────────────────────┘
              │
              ▼
┌─────────────────────────────────┐
│ INSPECT MASK PATTERN IN         │
│ ACCORDANCE WITH INSPECTION      │──S3
│ PROCESS OF PRESENT INVENTION    │
└─────────────────────────────────┘
              │
              ▼          S4
         ◇─────────────◇   NO
         ◇  DEFECT ?   ◇──────┐
         ◇─────────────◇      │
              │               │
             YES              │
              ▼               │
┌─────────────────────────────────┐  │
│     RECOVER DEFECT              │──S5
└─────────────────────────────────┘  │
              │◄──────────────┘
              ▼
         ╭─────────────╮
         │    END      │──S6
         ╰─────────────╯
```

FIG. 8

FIG. 9

FIG. 11A

FIG. 11B

FIG. 11C

FIG. 11D

FIG. 11E

FIG. 12

OBTAIN DIFFERENCE OF
CORRESPONDING PIXELS
OF STANDARD IMAGE
OR SHIFTED STANDARD
IMAGE WITH RESPECT TO
INSPECTION IMAGE   ∼S11

OBTAIN MAXIMUM VALUE
AND MINIMUM VALUE OF   ∼S12
DIFFERENCE

S13

DIFFERENCE
RESULT>   YES
MAXIMUM
VALUE

NO

OUTPUT VALUE OF
(DIFFERENCE RESULT)−(MAXIMUM VALUE)

S14

S15

DIFFERENCE
RESULT<   YES
MAXIMUM
VALUE

NO

OUTPUT VALUE OF
(DIFFERENCE RESULT)−(MINIMUM VALUE)

S16

OUTPUT VALUE "0"

S17   FIG. 13

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I declare:
that I verily believe myself to be the original, first and sole (if only one
individual inventor is listed below) or an original, first and joint inventor
(if more than one individual inventor is listed below) of the invention in

METHOD AND APPARATUS FOR INSPECTING PATTERNS

the specification of which is attached hereto unless the following box is
checked.

☐ was filed on _____ as United States Application
or PCT International Application No._____, and
was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above
identified specification, including the claims, as amended by any amendment
referred to above.
I acknowledge the duty to disclose information of which is material to pat-
entability as defined in 37 CFR 1.56.
I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365
(b) of any foreign application(s) for patent or inventor's certificate, or
35 U.S.C. 365(a) of any PCT International application which designated at
least one country other than the United States, listed below and have also
identified below any foreign application for patent or inventor's certifi-
cate, or PCT International application having a filing date before that of the
application on which priority is claimed:

Country	Category	Application No.	Filing Date	Priority Claim
Japan	Patent	11-089332	March 30, 1999	Yes
Japan	Patent	11-261912	September 16, 1999	Yes

And I hereby appoint Norman F. Oblon (Reg. No. 24,618), Marvin J.
Spivak (Reg. No. 24,913), C. Irvin McClelland (Reg. No. 21,124), Gregory
J. Maier (Reg. No. 25,599), Arthur I. Neustadt (Reg. No. 24,854), Richard
D. Kelly (Reg. No. 27,757), James D. Hamilton (Reg. No. 28,421), Eckhard
H. Kuesters (Reg. No. 28,870), Robert T. Pous (Reg. No. 29,099), Charles
L. Gholz (Reg. No. 26,395), Vincent J. Sunderdick (Reg. No. 29,004),
William E. Beaumont (Reg. No. 30,996), Robert F. Gnuse (Reg. No. 27,295),
Jean-paul Lavalleye (Reg. No. 31,451), Stephen G. Baxter (Reg. No. 32,884),
Robert W. Hahl (Reg. No. 33,893), Richard L. Treanor (Reg. No. 36,379),
Steven P. Weihrouch(Reg. No. 32,829), John T. Goolkasian(Reg. No. 26,142),
Richard L. Chinn (Reg. No. 34,305), Steven E. Lipman (Reg. No. 30,011),
Carl E. Schlier (Reg. No. 34,426), James J. Kulbaski (Reg. No. 34,648),
Richard A. Neifeld (Reg. No. 35,299), J. Derek Mason (Reg. No. 35,270),
Surinder Sachar (Reg. No. 34,423), Christina M. Gadiano (Reg. No. 37,628),
Jeffrey B. McIntyre (Reg. No. 36,867), Paul E. Rauch (Reg. No. 38,591),
William T. Enos(Reg. No. 33,128) and Michael E. McCabe, Jr., (Reg. No. 37,182)
each of whose address is Fourth Floor, 1755 Jefferson Davis Highway,
Arlington, Virginia 22202, or any one of them, my attorneys with full
power of substitution and revocation, to prosecute this application and
to transact all business in the Patent & Trademark Office connected
therewith, and request that correspondence be directed to Oblon, Spivak,
McClelland, Maier & Neustadt, P.C., Fourth Floor, 1755 Jefferson Davis
Highway, Arlington, Virginia 22202.

I declare further that all statements made herein of my own knowledge are
true and that all statements made on information and belief are believed to
be true; and further that these statements were made with the knowledge that
willful false statements and the like so made are punishable by fine or im-
prisonment, or both, under Section 1001 of Title 18 of the United States
Code and that such willful false statements may jeopardize the validity of
the application or any patent issued thereon.

DECLARATION FOR PATENT APPLICATION

I declare further that my post office address is at c/o Intellectual Property Division, KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura 1-chome, Minato-ku, Tokyo 105-8001, Japan; and that my citizenship and residence are as stated below next to my name:

Inventor: (Signature)	Date	Residence
Eiji Sawa Eiji Sawa	Date: MAR. 23. 2000 Citizen of: Japan	Yokohama-shi, Japan
Hiromu Inoue Hiromu Inoue	Date: MAR. 23. 2000 Citizen of: Japan	Yokohama-shi, Japan
Satoshi Imi Satoshi Imi	Date: MAR. 23. 2000 Citizen of: Japan	Hiratsuka-shi, Japan
	Date: Citizen of: Japan	
	Date: Citizen of: Japan	
	Date: Citizen of: Japan	
	Date: Citizen of: Japan	
	Date: Citizen of: Japan	